

## JL Industries Introduces a New Line of Rooftop Safety Railings for Roof Hatches and Smoke Vents.



### SAF-T-HATCH ROOFTOP Safety Rail (Patent Pending)

**Certifications:** Meets OSHA required compliance for safe egress and ingress through rooftop hatch openings while hatch is in use. Complies with OSHA CFR 29-1910.232 and CFR 29-1910.27.

**Construction:** Rail: 1-5/8" OD A53 grade B seamed galvanized steel with zinc plated post caps. The base is factory galvanized 2" x 2" 16 gauge seamed steel with cast steel hot dipped galvanized clamps.

**Guard:** Zinc-plated 3/16" ASTM chain with quick links and hoops or optional galvanized self-closing rigid gate.

**Finish:** Safety Yellow Powder Coating.

**Installation:** Quickly installs by a clamping frame around curb base of roof hatch or fire hatch. Does not require "approved" installer. Fits all brands of existing roof hatches with cap flashing-field adjustable to fit flashing size.

STH 1	30" x 36"	RHA/RHG 1
STH 2	54" x 30"	RHA/RHG 2
STH 3	96" x 30"	RHA/RHG 3
STH 4	36" x 36"	RHA/RHG 4
STH 5	48" x 48"	RHA/RHG 5
Custom Sizes Available Upon Request		

**ACTIVAR**  
INC.  
Construction Products Group

[www.activarcp.com](http://www.activarcp.com)

1-800-554-6077



JL@JLINDUSTRIES.COM